SUPERTRACK

Z10MK4

Ku-BAND Maritime VSAT Antenna

The SuperTrack Z-Series is the perfect solution for ships looking for broadband speeds at sea. Stay in touch with your networks via high speed access to the internet, email, multiple VoIP phones and more



*Design is subject to change without notice

MOST SELECTED VSAT MODEL

Most customers in worldwide maritime industry have chosen SUPERTRACK Z-Series as standard VSAT system for their vessels. The Z-Series MK4 will be a optimal satellite communication performance to your vessels.

EASY MAINTENANCE

The Z10MK4 has minimized parts and PCU integrated all electric parts in one module. This feature allows easier maintenance of operators and service providers.

GYRO FREE SUPPORTING

Z10MK4 can support your connection even the vessel does not have gyro(s) or in any case of the gyro failure. Z10MK4 will sustain your network communication with tracking performance without vessel failure status related.

COST AFFORDABLE

With all the latest innovations, SUPERTRACK Z-Series MK4 promise a product line-up which can fulfil all your needs at affordable costs.

RELIABILITY. THE BASIC VIRTUE

In the middle of sea, under various tough sea condition the most important factor or lifeline is high quality communication equipment with reliable connection, stable tracking and fast network performance. Live chatting with friends, video call with family, listening radio over IP, emergency phone calls and all kinds of communication to home-world require network sustainability with reliable equipment.

The SUPERTRACK is your reliable partner all the time.

PRODUCT KEY FEATURES

- In-built DVB-S2X Tuner Carrier SNR direct tracking is available
- Easy Maintenance with simple modular design All electrical control parts are integrated in one single module "PCU" for fast and easy maintenance.
- Web interface & Remote software upgrade Monitoring and Control (M&C) function and firmware upgrade fully supported via web interface.
- Graphic monitoring support Antenna signal strength or RSSD can be monitored

through web GUI via PC and other wireless device such as tablet PC and mobile phone.

Wi-Fi support

ACU can be operated by Wi-fi interface, a seamless wireless interface between user and ACU

- Proven LEO/MEO satellites tracking algorithm
- Option for single cable solution between ADU and BDU
- SNM support
- Automatic Satellite Search & Skew Control
- Accurate Signal Acquisition by KNS's Distinctive **Algorithm**
- Pre-programmed Satellite Database Editable 80 satellite data



Z10MK4 Ku -BAND Maritime VSAT Antenna

SPECIFICATIONS

ABOVE DECK

Dish Diameter 100cm (40")

144cm(D) x 152cm(H) Antenna Dimension

Antenna Weight 110 Kg

Frequency TX: 13.75 ~ 14.5 GHz

RX: 10.7 ~ 12.75 GHz

Antenna Gain TX: 41.0 dBi @ 14.25 GHz

RX: 40.0 dBi @ 11.75 GHz

18.89dB/k (in Radome) G/T

@ 30deg. Elevation angle and 11.75GHz, Clear Sky

Operating Platform 3 - Axis (Azimuth, Cross, Elevation)

LNB Universal LNB(4LO selectable PLL LNB)

BUC 8W

OpenAMIP Support **Skew Control** Automatic **Elevation Angle** -20° to 110°

Unlimited **Azimuth Angle Cross Angle** $\pm 35^{\circ}$

Ship Motion Roll: ±24° at 8-12 sec periods

> Pitch: ±14° at 6-12 sec periods Yaw: ±8° at 15-20 sec periods

Tracking Speed More than 90°/sec

Vibration Damper Rubber Damper Included

Antenna Input Power 48V DC 4.18A **Temperature** -20°C to +55°C Humidity Up to 100% @ 40°C

PACKING DIMENSION

Size 158 x 158 x 177 cm

Gross Weight 230Kg

Packed by Wooden Crate

CERTIFICATION/QUALIFICATION

Certification



 ϵ

RoHS

Satellite Approval

INTELSAT.

www.kns-kr.com

KNS Headquarters

1476-55, Yuseong-daero, Yuseong-gu, Daejeon South Korea (34055) Tel: +82 42 932 0351

Fax: +82 42 932 0353 E-mail: sales@kns-kr.com

BELOW DECK

KA - 190 Antenna Control unit



19" Rack 1U size **ACU Size**

Gyro Interface NMEA 0183, Synchro, Step by Step **Input Power** 100~240V AC, 8A/4A, 50~60 Hz

Out put Power 48VDC. 4.18A

External I/O RS-232C, RS-422, USB, Mini-USB,


Ethernet, Console

Monitoring Web Interface Support (SCS) Wi-fi Dongle Wi-fi access is available (Optional)

WARRANTY INFORMATION

3-year parts warranty

RADOME DIMENSION



KNS Malaysia Sales Office

20 Jalan Setia Tropika 9/15, Taman Setia Tropika, Johor, Malaysia

Tel: +60 1673 18407 E-mail: james@kns-kr.com

KNS Europe Sales Office

Carl-Zeiss Straße 4, 71093 Weil im Schönbuch, Germany

Tel: +49 1727 640 257 E-mail: fpollak@kns-kr.com

^{*}Specification is subject to change without notice